



# VULCAN 2 C

## Conventional Sounder/ Beacon

The VULCAN 2 C is a low consumption sounder designed to be used as an unobtrusive low profile sounder or as a base sounder to be installed in conjunction with a conventional detector. This leads to reduced installation costs and improves the aesthetics of the fire alarm system.

Four different tones are available and selected by jumpers. The Sound level can be adjusted if required, using the potentiometer.

The complete range is composed of 3 varieties in both base and wall mounted versions: Beacon, Sounder and combined Sounder/ Beacon.

### TECHNICAL SPECIFICATIONS

|                        |                         |
|------------------------|-------------------------|
| SUPPLY VOLTAGE         | 20 V to 30 V DC         |
| LOOP CURRENT - BEACON  | 2.5 mA                  |
| MAXIMUM SOUNDER OUTPUT | 96 dB (@ 1 m - 30 V DC) |
| MAX. CABLE SIZE        | 2.5 mm <sup>2</sup>     |
| OPERATING TEMPERATURE  | -10°C to 55°C           |
| MAX. HUMIDITY          | 95% RH Non-Condensing   |
| CASE MATERIAL          | ABS and Transparent PC  |
| COLOUR                 | Red or White            |
| DIMENSIONS             | 100 (D) x 29 (H) mm     |
| WEIGHT                 | 144 g inc. Lid          |

### ORDER CODE

|              |               |   |
|--------------|---------------|---|
| VULCAN 2 CS  | 1328-CPR-0289 | CONVENTIONAL BASE SOUNDER               |
| VULCAN 2 CSB | 1328-CPR-0289 | CONVENTIONAL BASE SOUNDER WITH ISOLATOR |
| VULCAN 2 CB  |               | CONVENTIONAL BEACON                     |
| VULCAN 2 L   |               | OPAQUE LID                              |
| VULCAN 2 LT  |               | TRANSPARENT LID                         |